



eni Rotra ATF II D

eni Rotra ATF II D is a special fluid mainly suitable in modern automatic transmissions and in many other applications where very low temperature performance, stability to mechanical loads and high Viscosity Index are required. **eni Rotra ATF II D** is specifically designed for filling and topping-up automatic transmissions built by makers who recommend the use of GM DEXRON II D type products.

CHARACTERISTICS (TYPICAL FIGURES)

eni Rotra ATF II D

Viscosity at 100°C	mm ² /s	7
Viscosity at 40°C	mm ² /s	34
Viscosity at -40°C	mPa.s	45000
Viscosity Index	-	183
Flash Point COC	°C	200
Pour Point	°C	-42
Colour	-	red
Mass density at 15°C	kg/l	0,865

PROPERTIES AND PERFORMANCE

- Careful selection of the Viscosity Index improver ensures excellent viscosity characteristics even after extended service.
- Its very low pour point guarantees excellent performance at the lowest service temperatures
- Its correctly balanced friction modifiers ensure quiet, smooth operation resulting in optimum transmission efficiency.
- **eni Rotra ATF II D** has an excellent oxidation stability thus preventing deterioration of components at very high temperatures and avoiding any sludge formation tendency.
- Its good detergent-dispersant properties help keep impurities in suspension preventing deposit formation.
- Its EP additives help minimize wear and guard against damage to gear surfaces.
- **eni Rotra ATF II D** is not corrosive to steel and copper and to ferrous and nonferrous alloys in general.
- Its antirust properties inhibit rust formation in the hydraulic systems of automatic transmissions.
- Its antifoam qualities minimize any tendency to foaming formation that could adversely affect oil circulation and lubricating properties.
- **eni Rotra ATF II D** is perfectly compatible with all types of rubber used in gaskets and seals.



eni Rotra ATF II D

SPECIFICATIONS

eni Rotra ATF II D is officially approved or meets the requirements of the following specifications:

- GM DEXRON IID
- FORD MERCON
- MAN 339 Typ V1
- MAN 339 Typ Z1 level
- MB 236.6 level
- VOITH H55.6335.xx (G 607, Diwa and Midimat)
- ZF TE-ML 04D, 11A, 14A
- ALLISON C4
- CATERPILLAR TO-2
- BMW
- RENK Doromat
- VICKERS 35VQ25
- LIEBHERR