



APPLICATIONS

Eni Acer 150 is a lubricant for circulation systems, oleodynamic circuits and air compressors where antirust and antioxidant properties are required.

Eni Acer 150 is particularly recommended for lubrication of journal and rolling bearings, crank mechanisms and gear couplings that are not demanding antiwear or E.P. performances, joints and wet clutches not for automotive applications.

CUSTOMER ADVANTAGES

- Quick separation from water that could accidentally enter the system thanks to optimal demulsive capacity
- Effective protection from rust and corrosion
- Oil film continuity and incompressibility ensured by a quick antifoam and air release action
- Compatibility with rubber types that are commonly used for seals

SPECIFICATIONS & APPROVALS

- DIN 51517-2 CL
- ISO-L-DAB
- DIN 51506 VBL
- ISO 11158 L-HL
- DIN 51524-1 HL
- AFNOR NF E 48600 HL
- BS 4231 HSC
- CETOP RP 91 H HL
- ANSI/AGMA 9005-E02
- ISO L-CKB





CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m ³	895
Viscosity at 40°C	ASTM D 445	mm ² /s	150
Viscosity Index	ASTM D 2270	-	97
Flash point (COC)	ASTM D 92	°C	243
Pour point	ASTM D 97	°C	-15
Demulsibility at 82°C	ASTM D 1401	mins	15
N.N.	ASTM D 974	mgKOH/g	0.08
Rust test/B	ASTM D 665	-	pass

WARNINGS

- **Eni Acer 150** must not be used in systems operating with lubrication in boundary conditions or where antiwear or E.P. performances are required.

